T06T+0'-Z95Z2Z60

FIG. 1



09272567 "04/09/07

FIG. 2A



TO6TH0" 29572760

FIG. 2B



TO6ThO' 7957276O



FIG. 3A

TO6TnO" 29572760



FIG. 3B

TD6THO"Z9SZZ60



FIG. 3C

TD6THO"29527760



FIG. 3D

T06T40' Z89Z2Z60



FIG. 3E

09727567.041901

FIG. 4



T06Th0'Z9572760



FIG. 5A

T06ThO* 29572760



FIG. 5B

09727567 .04190T



FIG. 5C

TO6THO" Z9572Z670

503



FIG. 5D

09727567 "0412801

506



FIG. 5E

09727567 "0412901

FIG. 6



FIG. 7


700
SLC
Handle (optional)
Enable
703
704
702
705
Name
Comment
SLA
Handle (optional)
ApplyTime
Create Time (SLC)
706
708
710
712
Apply<Day>
FromTime
ToTime
714
Name
Comment
Create Time (SLA)
716
718
720
724
726
728
730
ICMPMetric
SamplingInterval
PayloadSize
TOS
UDPMetric
SamplingInterval
PayloadSize
TOS
Port
DNSMetric
SamplingInterval
TestIPaddr
HTTPMetric
SamplingInterval
URLPath Port
ProxyServer
NameServer
CacheEnable
TOS
722
VoIPMetric
SamplingInterval
PacketsPerSample
InterPacketInterval
PayloadSize
EnableControl
TOS
SourcePort
TargetPort
<Metric>Threshold
AvgHourlyLatency
AvgDailyLatency
DailyAvailability
MonthlyAvailability
<Metric>Device Spec
736
CreateTime
TargetDevice
SourceDevice
734
VoIPThreshold
Jitter
RoundTripLatency
PacketLoss
732
Element
Attr1
Attr2 . . .
XML Element
Contains
Selection